

Limitations of MCM Panel applications:

NOW Specialties Inc. panel systems are wall panel systems that has been tested for use in a vertical application. Using the above mentioned system in a horizontal fashion such as tops of canopy, roofing applications or other, will not carry the NOW Inc. workmanship warranty that is normal with a vertical wall. Water penetration will be evident behind the panel system if used in a flat or sloped horizontal plane. NOW Inc. cannot be held liable for water infiltration or damage by improper use/application of the panel system.

MCM panels are not designed for foot traffic. MCM material can be easily damaged if not protected properly, especially when installed on a horizontal surface application. NOW IS NOT RESPONSIBLE FOR ANY DAMAGE TO THE MATERIAL OR FOR ANY AIR/WATER INFLITRATION AS A RESULT THEREOF.

When MCM panels are used for coping caps and in canopy or eyebrow roof applications, they can be easily damaged by the unprotected use of equipment such as safety lines and swing stage cables. NOW IS NOT RESPONSIBLE FOR ANY DAMAGE AT THESE CONDITIONS AS A RESULT THEREOF.

The NOW 3100 RR Dry joint system is NOT designed for any horizontal applications and is therefore not to be installed in any upward facing horizontal planes. At these conditions, the MCM panels will be installed using our NOW 1100 (Wet) system and all upward facing panel joints must be wet sealed.

NOW does not recommend the use of CEG (Continuous Edge Grip) extrusion systems in large soffit panel applications.